

# SPECTRO LUBRICANT TECHNICAL DATA

## Golden Semi-Synthetic Engine Oil



- EXCEPTIONALLY HIGH ANTI-WEAR ADDITIVE TREATMENT REDUCES WEAR.
- EXTENDS COMPONENT LIFE.
- TREMENDOUS LUBRICATION PROTECTION IN EXTREME HEAT CONDITIONS.
- PROVIDES LOWER CONSUMPTION RATE.
- EXCEPTIONAL OFF-SEASON PROTECTION OF INTERNAL PARTS.
- API SF/SG – JASO MA

### Description

Spectro Golden Semi-Synthetic is the ultimate semi-synthetic motor lubricant formulated specifically for use in high output, high performance engines. It incorporates a blend of the world's leading group IV synthetic base oils and superior quality petroleum base oils with the most advanced anti-wear additive system available for motorcycles.

### Application

Golden Semi-Synthetic should be used according to the manufacturer's recommended change intervals and viscosity. If in doubt, use the 10w40. No special steps need to be taken when switching to a semi-synthetic product.

### Typical Inspections

	10w40	20w50
Kinematic Viscosity @ 100° C cSt	15.3	19.6
Kinematic Viscosity @ 0° C cSt	97.2	155.0
Flash Point, °C	216	230
Pourpoint, °C	-27	-23
Viscosity Index	161	146

  

	10w30	15w50
Kinematic Viscosity @ 100° C cSt	11.5	17.2
Kinematic Viscosity @ 0° C cSt	79.5	138
Flash Point, °C	160	245
Pourpoint, °C	-31	-30
Viscosity Index	162	151

### Code

Code	Description	Weight
L.GS41030	12/1 Liter Bottles	25 Lbs.
L.GS41040	12/1 Liter Bottles	25 Lbs.
L.GS41550	12/1 Liter Bottles	25 Lbs.
L.GS42050	12/1 Liter Bottles	25 Lbs.
U.GS41030	4/4 Liter Bottles	36 Lbs.
U.GS41040	4/4 Liter Bottles	36 Lbs.
U.GS42050	4/4 Liter Bottles	36 Lbs.
Z.1040SYN	55 gal drum	450 Lbs.
Z.2050SYN	55 gal drum	450 Lbs.

SPECTRO OILS OF AMERICA  
993 Federal Rd., Brookfield, CT 06804  
203-775-1291 Fax 203-775-8720  
[www.spectro-oils.com](http://www.spectro-oils.com)

