

04/08/2011

## Spectro Tech Bulletin HD-1

Heavy Duty Fork Oil Informational Chart

PRODUCT	WEIGHT	VISCOSITY @ 100° C
Harley Type B	10wt	5.51
Harley Type E	20wt	7.95
Screaming Eagle Type Heavy	20wt	8.60
Screaming Eagle Type Extra Heavy	60wt	24.49
Spectro Type E	20wt	7.93
Spectro Type Heavy	40wt	13.06

VISCOSITY @ 100° C HYDRAULIC OILS	
SAE GRADE	RANGE (cST)
5	3.80-4.09
10	4.10-5.59
20	5.60-9.29
30	9.30-12.49
40	12.50-16.29
50	16.30-21.89
60	21.90-26.09

**USE OF SPECTRO PRODUCTS WILL SAFEGUARD YOUR WARRANTY**

\*Magnuson-Moss Warranty Improvement Act Title 15 Commerce and Trade, Chapter 50 Sec. 15

Spectro Oils of America hereby states that it meets all American Made Motorcycle Manufacturer's warranty requirements set forth by the motorcycle manufacturer. Remember, choosing an alternative to the O.E.M. is not only allowed by the manufacturer, it is your right as a consumer. USE OF THIS PRODUCT WILL NOT VOID YOUR WARRANTY. \*You must follow the directions for engine break-in and maintenance as explained in your owner's manual. This oil is compatible with other modern oils and will mix readily unless specified by the manufacturer.

